


伸銅品

りん脱酸銅 C1220・C1201

▶ 比重 8.94




銅(Cu)99.90%以上、りん(P)0.015~0.040%を含む純銅。酸素量が少ないので水素脆化もなく、耐食性、耐候性、絞り加工性、熱伝導性(熱伝導率80%前後→りん(P)が伝導性を妨げる)に優れています。風呂釜、屋根板などに使用されています。



伸銅品

りん脱酸銅管 コイル(C1220)



各種サイズ		長さ(M)	調質			備考
寸法 (a × t mm)			H	1/2H	O	
2.0	× 0.4	20M			◇	
	× 0.5				◇	
3.0	× 0.5				◇	
	× 0.75				◇	
	× 1.0				◇	
3.18	× 0.5				◇	
	× 0.8				◇	
4.0	× 0.5				◇	
	× 0.6				◇	
	× 0.8				◇	
	× 1.0				◇	
4.76	× 0.8				◇	
5.0	× 0.8				◇	
	× 1.0				◇	
6.0	× 0.8				◇	
	× 1.0				◇	
	× 1.5				◇	
6.35	× 0.8				◇	
	× 1.0				◇	
8.0	× 0.8				◇	
	× 1.0			◇		
	× 1.2			◇		
	× 1.5			◇		
	× 2.0			◇		
9.53	× 0.8			◇		
	× 1.0			◇		
	× 1.2			◇		
	× 1.5			◇		
10.0	× 0.8			◇		
	× 1.0			◇		
	× 1.2			◇		
	× 1.5			◇		
	× 2.0			◇		
12.0	× 1.0			◇		
	× 1.2			◇		
	× 1.5			◇		
	× 2.0			◇		
12.7	× 0.8			◇		
	× 1.0			◇		
	× 1.2			◇		
	× 1.5			◇		
14.0	× 1.0			◇		
15.0	× 1.0			◇		
	× 1.2			◇		
	× 1.5			◇		
15.88	× 0.8			◇		

りん脱酸銅管 コイル(C1220)

各種サイズ		長さ(M)	調質			備考
寸法(a × t mm)			H	1/2H	O	
15.88	× 1.0	20M			◇	
	× 1.2				◇	
	× 1.5				◇	
16.0	× 1.0				◇	
	× 1.5				◇	
	× 2.0				◇	
19.05	× 1.0				◇	
	× 1.2				◇	
	× 1.5				◇	
20.0	× 1.2			◇		
	× 2.0	25M			◇	
22.23	× 1.0	20M			◇	
25.4	× 1.2			◇		

◇手配品